

Bus bodybuilder 3D Request KC series

Delivery time can be up to 2 weeks depending on workload, complexity of request and priority of the project. (Be sure to fill in the form as accurate as possible, it affects the delivery time.) Please fill in the scope of the model and one of the listed options of references below.

All instances marked with (*) must be filled in.

Requester*: _____ Bus bodybuilder: _____

Date of request: Requested delivery date*: _____

Reason for 3D: _____

Output format*:

STEP (Preferred)

CAT Part (CATIA V5 R30 native)



Non-disclosure agreement (NDA): Yes

1. Area of interest (reduces lead-time)*:

Complete chassis

Complete **FRONT** module

Drivers Area (inc Electrical panel)

Frames

Axle Components

Steering & hydraulics Fuel tanks

Complete **CENTRE** module (High- or Low-articulated?)

Complete **REAR** module

Frames

Driven Axle Comp TAG Axle Comp

Engine Comp (Simplified/Outer components)

Gearbox (Simplified/Outer components)

Cooling System (inc heating conn.)

Air Inlet System

Exhaust System

Complete **ROOF** module

Auxiliary box

2. Reference:

Option A: Chassis Number (A-order only)

CHASSIS #:

Option B: Main dimension drawing (MDD)

Note: The 3D model delivered may not cover the complete specification of the chassis.

Drawing #:

Configuration:

Customer choices*:

DRIVERS AREA

Instrument Panel

- FIP (110 / 80 mm)
- AIP
- AIP Extended

Brake control

- Electronic
- Pneumatic

Steering wheel position

- LHD
- RHD

FRONT

- Battery Tray
- Spare Wheel Carrier
- Fuel specification (volume, filling side and filler neck pos.)
- Wheel chair adaptation
- Electro Hydraulic Steering (EHS)

REAR

- Gearbox ZF Eco Life
- Gearbox GR (K-chassis)
- Exhaust direction
 - Rear
 - Right
 - Left
- Ac-prep (chassis mounted)
 - Pulley 230
 - Pulley 280
- Draw beam
- SCR-tank
 - 45 dm³ (Eu6, LHS only)
 - 80 dm³ (Eu6, LHS only)
- Door prep. (C-chassis)
 - With rear door
 - Without rear door
- Width of cr. member rear axle front (K-chassis)
 - 2410 mm
 - 2300 mm
- Inverter position (K-chassis, Hybrid model)
 - Front position
 - Rear position
- Height of the cross member behind tag axle (K-chassis)
 - Z0+400 mm
 - Z0+520 mm
 - Z0+450 mm

NOTES

Send form to busbuilderhelp.sweden@scania.com for processing your order and we will get back to you.